

# CYCLE DIM T8

## ELECTRONIC DIMMING BALLAST FOR T8/TLD FLUORESCENT LAMPS




### FEATURES

- ➔ Not require dimming control wires.
- ➔ 5%-100% dimming range.
- ➔ Give the most economy way of fluorescent dimming system
- ➔ Prolong lamp life with Super Soft Start™ mode.
- ➔ Recommended for lobbies, theaters, stadiums, meeting rooms and hotels.

### LAMPS

T8/(G13)



### BALLAST SPECIFICATION

Safety Input Voltage Range	154 to 265 Volts
Operating Input Voltage	198 to 255 Volts
Power Factor	0.6
DC Voltage Operation	175 to 240 Volts DC
Maximum Case Temperature (tc)	90°C
Environmental Operating Temperature (ta)	15 to 50°C
Maximum Relative Humidity	90% non - condensing
Safety	IEC 61347-1, IEC 61347-2-3
Guaranteed Withstanding Voltage	1800 Vac
Insulation Resistance	>2 MΩ
Endurance	IEC 60929
De-activated Lamp Protection	Automatic Restart
Removal of Lamp	IEC 60929

End of Lamp Life Protection	Automatic Restart
Electromagnetic Compatibility (EMC)	CISPR 15
Immunity	IEC 61547 ( EN 61000-4-2/-3/-4/-5/-6/-11 )
Main Transient Over Voltage	IEC 60929
Lamp Current Crest Factor	<1.7
Lamp Flicker	Flicker Free
Output Frequency	25 to 100 kHz
Ballast Lumen Factor	0.95
Lamp Starting	Super Soft Start Within 2 sec.
Lamp Cable Length	1.5m.(maximum)
Dimming Range	5% to 100%
Case & Connection	Aluminum & Terminal Block



